



AU-D5N/5

SPECIFICATION

HOUSING :HIGH COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES

SURFACE TREATMENT :ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT POLYESTER POWDER COAT

REFLECTOR :HIGH GRADE ANODIZED ALUMINIUM (DIAMOND)

DIFFUSER :CLEAR AND FROSTED GLASS


FRAME :STEEL WITH POLYESTER POWDER COAT

COLOR :WHITE

PROTECTION CLASS :PROTECTION CLASS EQUIVALENT TO IP 44

INSTALLATION :RECESS T-BAR CEILING, RECESS CONCEAL

APPLICATION :BUILDING, HOSPITAL, DEPARTMENT STORE, HOTEL CONDOMINIUM, RESTAURANT, SHOP, RESIDENTIAL ETC.



MODEL	DIMENSION(mm.)		CUT OUT C (mm.)	LAMP HOLDER	LUMED (MAX)	LAMP TYPE
	Ø	H				
AU-D5N/5	178	185	155	E 27	1550 lm.	PL 14, 18, 20, 23W.
				E 27	13500 lm.	MH 70 , 100, 150W
				G 23	600 lm.	PLS 9W.
				G 24	1800 lm.	PLC 13, 18, 26W.

WIRES

<input type="checkbox"/> THW	<input type="checkbox"/> 70 °C	<input type="checkbox"/> 0.5 SQmm.	<input type="checkbox"/> 13 AWG
<input type="checkbox"/> UL STYLE & CSA TYPE	<input type="checkbox"/> 90 °C	<input type="checkbox"/> 1.0 SQmm.	<input type="checkbox"/> 15 AWG
<input type="checkbox"/> HEATER WIRE	<input type="checkbox"/> 105 °C	<input type="checkbox"/> 1.5 SQmm.	<input type="checkbox"/> 17 AWG
<input type="checkbox"/> OTHER	<input type="checkbox"/> 200 °C	<input type="checkbox"/> 2.5 SQmm.	<input type="checkbox"/> 20 AWG