




**AU-DN5-19**

**SPECIFICATION**

HOUSING	:HIGH COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES	COLOR	:WHITE
SURFACE TREATMENT	:ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT POLYESTER POWDER COAT	PROTECTION CLASS	:PROTECTION CLASS EQUIVALENT TO IP 54
REFLECTOR	:HIGH GRADE ANODIZED ALUMINIUM (POLISHED)	INSTALLATION	:RECESS CONCEAL CEILING
DIFFUSER	:FROSTED GLASS	APPLICATION	:BUILDING, HOSPITAL, DEPARTMENT STORE, HOTEL CONDOMINIUM, RESTAURANT, SHOWROOM SHOP, RESIDENTIAL ETC.
FRAME	:STEEL WITH POLYESTER POWDER COAT		



MODEL	DIMENSION(mm.)		CUT OUT C (mm.)	LAMP HOLDER	LUMED (MAX)	LAMP TYPE
	Ø	H				
AU-DN5-19	195	120	175	E 27 x 1	800 lm.	1 x PL 8, 11, 14,18W.
				E 27 x 2	800 lm.	2 x PL 8, 11, 14,18W.
				G 23 x 1	600 lm.	1 x PLS 7, 9W.
				G 23 x 2	600 lm.	2 x PLS 7,9W.
				G 24 x 1	1200 lm.	1 x PLC 13, 18W.
				G 24 x 2	1200 lm.	2 x PLC 13, 18W.