



AU-DN5-23-E27

SPECIFICATION

HOUSING :HIGH COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES

SURFACE TREATMENT :ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT POLYESTER POWDER COAT

REFLECTOR :HIGH GRADE ANODIZED ALUMINIUM (POLISHED)

DIFFUSER :FROSTED GLASS


FRAME :STEEL WITH POLYESTER POWDER COAT

COLOR :WHITE

PROTECTION CLASS :PROTECTION CLASS EQUIVALENT TO IP 54

INSTALLATION :RECESS CONCEAL CEILING

APPLICATION :BUILDING, HOSPITAL, DEPARTMENT STORE, HOTEL CONDOMINIUM, RESTAURANT, SHOWROOM SHOP, RESIDENTIAL, ETC.




MODEL	DIMENSION(mm.)		CUT OUT C (mm.)	LAMP HOLDER	LUMED (MAX)	LAMP TYPE
	Ø	H				
AU-DN5-23-E27	230	122	200	E 27 x 1	1550 lm.	1 x PL 18, 20, 23W.
				E 27 x 2	1550 lm.	2 x PL 18, 20, 23W.



AU-DN5-23-PL

SPECIFICATION

HOUSING	:HIGH COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES	COLOR	:WHITE
SURFACE TREATMENT	:ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT POLYESTER POWDER COAT	PROTECTION CLASS	:PROTECTION CLASS EQUIVALENT TO IP 54
REFLECTOR	:HIGH GRADE ANODIZED ALUMINIUM (POLISHED)	INSTALLATION	:RECESS CONCEAL CEILING
DIFFUSER	:FROSTED GLASS	APPLICATION	:BUILDING, HOSPITAL, DEPARTMENT STORE, HOTEL CONDOMINIUM, RESTAURANT, SHOWROOM SHOP, RESIDENTIAL, ETC.
FRAME	:STEEL WITH POLYESTER POWDER COAT		



MODEL	DIMENSION(mm.)		CUT OUT C (mm.)	LAMP HOLDER	LUMED (MAX)	LAMP TYPE
	Ø	H				
AU-DN5-23-PL	230	162	200	G 23 x 1	600 lm.	1 x PLS 7, 9W.
				G 23 x 2	600 lm.	2 x PLS 7, 9W.
				G 24 x 1	1800 lm.	1 x PLC 13, 18, 26W.
				G 24 x 2	1800 lm.	2 x PLC 13, 18, 26W.
				G 24 x 1	3200 lm.	1 x PLT 32, 42W.
				G 24 x 2	3200 lm.	2 x PLT 32, 42W.