



AU-DQ-B3

SPECIFICATION

HOUSING	:HIGH COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES	COLOR	:WHITE, BLACK
SURFACE TREATMENT	:ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT POLYESTER POWDER COAT	PROTECTION CLASS	:PROTECTION CLASS EQUIVALENT TO IP 20
REFLECTOR	:HIGH GRADE ANODIZED ALUMINIUM (LINE AND SANDBLAST, DIAMOND)	INSTALLATION	:RECESS CONCEAL CEILING
FRAME	:STEEL WITH POLYESTER POWDER COAT	APPLICATION	:BUILDING, HOSPITAL, DEPARTMENT STORE, HOTEL CONDOMINIUM, RESTAURANT, SHOWROOM SHOP, RESIDENTIAL, ETC.

MODEL	DIMENSION(mm.)			CUT OUT(mm.)		LAMP	LUMEN	LAMP TYPE
	L	W	H	L	W	HOLDER	(MAX)	
AU-DQ-B3	325	130	140	305	110	E 27 x 3	800 lm.	3 x PL 8, 11, 14W.
						G 23 x 3	400 lm.	3 x PLS 7
						G 24 x 3	900 lm.	3 x PLC 13

