



AU-DQ

SPECIFICATION

HOUSING :HIGH COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES

SURFACE TREATMENT :ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT POLYESTER POWDER COAT

FRAME :STEEL WITH POLYESTER POWDER COAT (WHITE, BLACK, SILVER)

LAMP RING :STEEL WITH POLYESTER POWDER COAT (WHITE, BLACK, SILVER)

PROTECTION CLASS :PROTECTION CLASS EQUIVALENT TO IP 20

INSTALLATION :RECESS CONCEAL CEILING

APPLICATION :BUILDING, HOSPITAL, DEPARTMENT STORE, HOTEL RESTAURANT, SHOWROOM, SHOP, RESIDENTIAL ETC.

MODEL	DIMENSION(mm.)			CUT OUT(mm.)		LAMP	LUMEN	LAMP TYPE
	L	W	H	L	W	HOLDER	(MAX)	
AU-DQ-Q3	495	205	90	470	180	G 53 x 3	48000 cd.	3 x QR111 12V. 50, 75, 100W.
AU-DQ-Q4	640	205	90	620	180	G 53 x 4	48000 cd.	4 x QR111 12V. 50, 75, 100W.
AU-DQ-Q4X	350	350	90	330	330	G 53 x 4	48000 cd.	4 x QR111 12V. 50, 75, 100W.

