



AU-DQ01G

SPECIFICATION

HOUSING :HIGH COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES

SURFACE TREATMENT :ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT POLYESTER POWDER COAT

REFLECTOR :HIGH GRADE ANODIZED ALUMINIUM (POLISHED)

DIFFUSER :FROSTED GLASS

FRAME :DIE-CAST ALUMINIUM

COLOR :WHITE, BLACK, SILVER

PROTECTION CLASS :PROTECTION CLASS EQUIVALENT TO IP 44

INSTALLATION :RECESS CONCEAL CEILING

APPLICATION :BUILDING, HOSPITAL, DEPARTMENT STORE, HOTEL CONDOMINIUM, RESTAURANT, SHOP, RESIDENTIAL ETC.

MODEL	DIMENSION(mm.)			CUT OUT(mm.)		LAMP	LUMED	LAMP TYPE
	L	W	H	L	W	HOLDER	(MAX)	
AU-DQ01G	125	125	183	110	110	E 27 x 1	800 lm.	1 x PL 8, 11, 14W.
						G 23 x 1	600 lm.	1 x PLS 7, 9W.
						G 24 x 1	1200 lm.	1 x PLC 13,18W.

