
light PLUS

FLUORESCENT


WIRE GUARD BATTEN TYPE



LPF G1-220-240

SPECIFICATION

HOUSING	:HIGH GRADE COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES
SURFACE TREATMENT	:ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT WHITE POLYESTER POWDER COAT
REFLECTOR	:WHITE STOVED ENAMELLED WIRE GUARD
WIRES	:THW, TIS.11-1988 STANDARD
LAMP HOLDER W/P	:SPRING LOCKED TYPE HIGH-HEAT RESISTANCE, TIS344-1987 STANDARD
STARTER HOLDER	:ROTOR LOCKED TYPE HIGH-HEAT RESISTANCE, TIS344-1987 STANDARD
PROTECTION CLASS	:PROTECTION CLASS EQUIVALENT TO IP 20
INSTALLATION	:SURFACE MOUNT OR SUSPEND MOUNT
APPLICATION	:FACTORY, WAREHOUSE, CARPARK, ETC.
COMPLETE SET*	:INCLUDING BALLAST, LAMP, STARTER NORMAL FOR T8 LAMP
	:INCLUDING ELECTRONIC BALLAST FOR T5 LAMP



MODEL	LAMP	DIMENSION(mm.)			WEIGHT
		L	W	H	(kg.)
LPF G1-220	2 x 18W. T8	635	127	118	3.75
LPF G1-240	2 x 36W. T8	1245	127	118	5.80

INSTALLATION : SURFACE MOUNT OR SUSPEND MOUNT