light PLUS

FLUORESCENT

ACRYLIC DIFFUSER TYPE

CLEAR

STIPPLE

OPAL


PRISMATIC



LPFTM2P

SPECIFICATION

HOUSING	:HIGH GRADE COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES
SURFACE TREATMENT	:ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT WHITE POLYESTER POWDER COAT
REFLECTOR	:PARABOLIC HIGH PURITY ANODIZED ALUMINIUM 99.85% MIRROR FINISH, TOTAL REFLECTION 87% (DIN 5063-3) FORM GERMANY
(OPTIONAL)	:PARABOLIC HIGH PURITY ANODIZED ALUMINIUM 99.99% MIRROR FINISH, TOTAL REFLECTION 95% (DIN 5063-3) FORM GERMANY
DIFFUSER	:OPAL ACRYLIC (OP), CLEARACRYLIC (CL), STIPPLE ACRYLIC (ST), PRISMATIC ACRYLIC (PR)
FRAME	:WHITE ENAMEL STEEL FRAME, EXTRUDE ALUMINIUM TRIM (OPTIONAL), SILICONE GASKET (OPTIONAL) WEATHER PROOF GASKET (OPTIONAL)
WIRES	:THW, TIS.11-1988 STANDARD
LAMP HOLDER	:ROTOR LOCKED TYPE HIGH-HEAT RESISTANCE, TIS344-1987 STANDARD
STARTER HOLDER	:ROTOR LOCKED TYPE HIGH-HEAT RESISTANCE, TIS344-1987 STANDARD
PROTECTION CLASS	:PROTECTION CLASS EQUIVALENT TO IP 54
INSTALLATION	:RECESS T-BAR CEILING, RECESS CONCEAL CEILING
APPLICATION	:OFFICE BUILDING, HOSPITAL, DEPARTMENT STORE UNIVERSITY, RESTAURANT, GOVERNMENTAL BUILDING, FACTORY, SHOP, WAREHOUSE, RESIDENTIAL, TOILET, CANTEEN, CLEAN ROOM, ETC.
COMPLETE SET*	:INCLUDING BALLAST, LAMP, STARTER NORMAL FOR T8 LAMP



SHEET STEEL THICKNESS

☐ 0.6 mm. ☐ 0.7 mm. ☐ 0.8 mm.

LAMP HOLDER

☐ ROTOR LOCKED TYPE

☐ SPRING LOCKED TYPE

REFLECTOR

☐ TOTAL REFLECTION 87 %

☐ TOTAL REFLECTION 95 %

WIRES

☐ THW	☐ 70°C	☐ 0.5 SQmm.	☐ 13 AWG
☐ UL STYLE & CSA TYPE	☐ 90°C	☐ 1.0 SQmm.	☐ 15 AWG
☐ HEATER WIRE	☐ 105°C	☐ 1.5 SQmm.	☐ 17 AWG
☐ OTHER	☐ 200°C	☐ 2.5 SQmm.	☐ 20 AWG

MODEL	LAMP	DIMENSION(mm.)			CUT OUT(mm.)		WEIGHT
		L	W	H	L	W	(kg.)
LPFTM2P-120A	1 x 18W. T8	595	200	80	580	180	2.70
LPFTM2P-120B	1 x 18W. T8	595	295	80	580	280	3.90
LPFTM2P-220A	2 x 18W. T8	595	295	80	580	280	4.30
LPFTM2P-220B	2 x 18W. T8	595	595	80	580	580	6.80
LPFTM2P-140A	1 x 36W. T8	1195	200	80	1180	180	4.60
LPFTM2P-140B	1 x 36W. T8	1195	295	80	1180	280	6.10
LPFTM2P-240A	2 x 36W. T8	1195	295	80	1180	280	6.90
LPFTM2P-240B	2 x 36W. T8	1195	595	80	1180	580	10.10

INSTALLATION : RECESS T-BAR CEILING, RECESS CONCEAL CEILING (M-BAR)