



AUFTM2P

SPECIFICATION

HOUSING :HIGH GRADE COLD-ROLLED STEEL SHEET FORMED BY HIGH QUALITY MACHINES

SURFACE TREATMENT :ION-PHOSPHATE AND ANTI-RUST FINISHED WITH UV RESISTANT WHITE POLYESTER POWDER COAT

REFLECTOR :PARABOLIC HIGH PURITY ANODIZED ALUMINIUM 99.85% MIRROR FINISH, TOTAL REFLECTION 87% (DIN 5063-3) FORM GERMANY

(OPTIONAL) :PARABOLIC HIGH PURITY ANODIZED ALUMINIUM 99.99% MIRROR FINISH, TOTAL REFLECTION 95% (DIN 5063-3) FORM GERMANY

DIFFUSER :OPAL ACRYLIC (OP), CLEARACRYLIC (CL), STIPPLE ACRYLIC (ST), PRISMATIC ACRYLIC (PR)

FRAME :WHITE ENAMEL STEEL FRAME, EXTRUDE ALUMINIUM TRIM (OPTIONAL), SILICONE GASKET (OPTIONAL) WEATHER PROOF GASKET (OPTIONAL)

WIRES :THW, TIS.11-1988 STANDARD

LAMP HOLDER :ROTOR LOCKED TYPE HIGH-HEAT RESISTANCE, TIS344-1987 STANDARD


STARTER HOLDER :ROTOR LOCKED TYPE HIGH-HEAT RESISTANCE, TIS344-1987 STANDARD

PROTECTION CLASS :PROTECTION CLASS EQUIVALENT TO IP 54

INSTALLATION :RECESS T-BAR CEILING, RECESS CONCEAL CEILING

APPLICATION :OFFICE BUILDING, HOSPITAL, DEPARTMENT STORE UNIVERSITY, RESTAURANT, GOVERNMENTAL BUILDING, FACTORY, SHOP, WAREHOUSE, RESIDENTIAL, TOILET, CANTEEN, CLEAN ROOM, ETC.

COMPLETE SET* :INCLUDING BALLAST, LAMP, STARTER NORMAL FOR T8 LAMP



SHEET STEEL THICKNESS

- 0.6 mm. 0.7 mm. 0.8 mm.

LAMP HOLDER

- ROTOR LOCKED TYPE
 SPRING LOCKED TYPE

REFLECTOR

- TOTAL REFLECTION 87 %
 TOTAL REFLECTION 95 %

WIRES

<input type="checkbox"/> THW	<input type="checkbox"/> 70°C	<input type="checkbox"/> 0.5 SQmm.	<input type="checkbox"/> 13 AWG
<input type="checkbox"/> UL STYLE & CSA TYPE	<input type="checkbox"/> 90°C	<input type="checkbox"/> 1.0 SQmm.	<input type="checkbox"/> 15 AWG
<input type="checkbox"/> HEATER WIRE	<input type="checkbox"/> 105°C	<input type="checkbox"/> 1.5 SQmm.	<input type="checkbox"/> 17 AWG
<input type="checkbox"/> OTHER	<input type="checkbox"/> 200°C	<input type="checkbox"/> 2.5 SQmm.	<input type="checkbox"/> 20 AWG

MODEL	LAMP	DIMENSION(mm.)			CUT OUT(mm.)		WEIGHT (kg.)
		L	W	H	L	W	
AUFTM2P-120A	1 x 18W. T8	595	200	80	580	180	2.70
AUFTM2P-120B	1 x 18W. T8	595	295	80	580	280	3.90
AUFTM2P-220A	2 x 18W. T8	595	295	80	580	280	4.30
AUFTM2P-220B	2 x 18W. T8	595	595	80	580	580	6.80
AUFTM2P-140A	1 x 36W. T8	1195	200	80	1180	180	4.60
AUFTM2P-140B	1 x 36W. T8	1195	295	80	1180	280	6.10
AUFTM2P-240A	2 x 36W. T8	1195	295	80	1180	280	6.90
AUFTM2P-240B	2 x 36W. T8	1195	595	80	1180	580	10.10

INSTALLATION : RECESS T-BAR CEILING, RECESS CONCEAL CEILING (M-BAR)